City of Colstrip – Building Division - Residential Plan Checklist

Locat	tion: Permit # _	
	er:	
Site	Foundation	
	_ Setbacks	Size of footing
	_ Floodplain or location rims	Keyway/rebar
	_ Parking provided	Depth of footing 42" min.
	& r	Foundation drainage/drain tile
Fram	ning	Rebar 8' walls/ #4 – 18" or #5 – 28"
	Qualify headers, beams, etc.	Anchor Bolts 1/2" x 10" at 6' O.C.
	Check size and spans of all structural members	
	_ Fire blocking	Damproofing for rooms below grade
	_ Draft stops	Crawl space vents and access
	Cantilevers over 2" require engineering	1
	Wall bracing per 602.10	Floor Plans
	_ Stud size/spacing/height	Bedroom egress/basement egress
	Deck detail	Smoke Detectors
	Double trimmers at header/beam	Dryers 14' limit
		Safety glazing/tub
Stair	S	Bathroom ventilation/laundry
ventil	lation	·
	_ Rise and run/nosings	Combustion air/outside air
	Height 6'8" – width 36"	Mechanical/location
	_ Handrails and guardrails	Fireplaces
	_ Winders/circulars per code	Attic access
	_ Illumination and activation	
	_Landings	
Section	onals	Garages
	Height clearances 7'6" minimum	Sheetrock separation
	_ Qualify materials for exterior cover	Garage door footing
	Prescriptive insulation/or trade off	Rated door or 13/8 solid core door
	_ Roof cover min. requirements and truss clips	No entry to bedrooms
Speci	ial Circumstances	
	Foam plastic location and flame spread limits	
	_ Dwelling unit separation/Cornice	
	_ All non-traditional require design	